

Product Details

P1002 Perforated Domed Grating

Technical Data

**Dimensions:**

195 dia. at finish level

40 - Overall Height

Connection - D10-D12 series vari-level gully body

Free Area - 115cm²

Materials - Stainless steel

Weight - 1.3 kg

General Description:

195 Dia. Stainless Steel Planting Area / Roof Garden Perforated Domed Grating, for use with soil / planting areas (For applications with asphalt membrane, where all drainage is concealed by soil). Provides drainage of moisture in planting areas and flower boxes, minimising loss of soil.

Materials:

Stainless Steel - Austenitic Grade 304 (Grade 316 optional on most products): Used for bodies, gratings, funnels, access covers, filter buckets and fixings. A corrosion-resistant metal containing significant amounts of nickel and chromium; AISI grade 304 stainless steel is used as standard, which is suitable for general use in and around buildings including most coastal locations. In applications such as swimming pools or having an aggressive atmosphere, grade 316 is recommended and is available optionally (if available, code 'M' will be listed under 'Options'). An even higher grade may be required for applications in highly corrosive environments including where exposure to seawater may be anticipated. Clean with soap and warm water rinse and wipe dry. Gratings may also be cleaned in certain dishwashers. Under no circumstances treat with metal scouring pads, metal scrapers or wire wool as these will contaminate surfaces leaving rust spots. Take care to cover stainless steel items when site work is going on, to avoid contamination with rust-inducing particles such as when mild steel or cast iron items are being cut.

All dimensions are in millimetres unless stated. In line with general practice all dimensions shown are nominal.

Wade International

Third Avenue, Halstead, Essex, CO9 2SX.

Telephone: +44 (0)1787 475151

Fax: +44 (0)1787 475579

e-mail: wadetech@alumascwms.co.uk

website: <https://www.alumascwms.co.uk/brands/wade/>

Typical Installation for P1002:

Note: This illustration may show a similar Wade Product - it is intended to show the general installation type only.

