

Product Details

C.C Membrane Clamping Collar



Technical Data

Dimensions:

188 dia. overall size

24 - depth

-30 to 10 - add to overall grating/cover height for min/max height between body flange and FFL

Connection - C series vari-level gully body

Materials - Cast iron, lacquered

Weight - 1 kg

General Description:

Cast Iron C series Vari-Level Membrane Clamping Collar (To fit C series Vari-Level gully bodies. Has 4" NPSM thread to accept 4" throat Vari-Level Gratings/Access Covers/Funnels. Gasket included.).

Options:

To specify an option, add option letter(s) as a suffix to the Spec. Code

W - weepholes (provide supplementary drainage at membrane level)

Materials:

Cast Iron - BS EN 1561: Used for bodies, membrane clamping collars, spigot adaptors and accessories such as extensions. A widely used metal in the drainage industry, its resistance to corrosion permits extended use under extreme conditions. Castings are coated with a high grade lacquer paint to provide internal and external surface coverage. Paint will gradually wear off and is replaceable; oxidisation (surface rusting) is a natural process which does not weaken the material. A zinc anti-corrosion coating is applied to certain castings by sherardizing.

All dimensions are in millimetres unless stated. In line with general practice all dimensions shown are nominal.

Wade International

Third Avenue, Halstead, Essex, CO9 2SX.

Telephone: +44 (0)1787 475151 Fax: +44 (0)1787 475579

e-mail: wadetech@alumascwms.co.uk website: <https://www.alumascwms.co.uk/brands/wade/>

Dimensioned Section for C.C:

