

Product Details

K2302 Grating



Technical Data

Dimensions:

160 dia. at finish level

176 dia. overall size

60 - Overall Height

Connection - 4" NPSM Vari-Level thread

Free Area - 48cm²

Materials - Grating - nickel bronze; Frame - cast iron, sherardized

Load Rating Class - L15

Weight - 2 kg

General Description:

160 Dia. Nickel Bronze Vari-Level Grating, for use with flexible sheet floor covering (eg. vinyl) (Open Grating), with 4" NPSM dia. vertical outlet. Durable, superbly finished items particularly suited to a high volume of pedestrian traffic.

Options:

To specify an option, add option letter(s) as a suffix to the Spec. Code
H - fitted with Pin Torx screws for security applications

Materials:

Cast Iron - BS EN 1561: Used for bodies, membrane clamping collars, spigot adaptors and accessories such as extensions. A widely used metal in the drainage industry, its resistance to corrosion permits extended use under extreme conditions. Castings are coated with a high grade lacquer paint to provide internal and external surface coverage. Paint will gradually wear off and is replaceable; oxidisation (surface rusting) is a natural process which does not weaken the material. A zinc anti-corrosion coating is applied to certain castings by sherardizing.

Nickel Bronze - BS EN 1982: Used with satin finish for gratings, funnels and access covers. A cast alloy with a fine grain effect which blends well with most floor finishes. The satin finish is generally maintained by the slight abrasive action of passing traffic. In unused areas the material will gradually tarnish. To restore lustre, apply a plain nylon scouring pad (not soap-filled) in the direction of grain. **Note: Avoid covering nickel bronze items with plastic sheeting after installation, otherwise blackening may occur.**

All dimensions are in millimetres unless stated. In line with general practice all dimensions shown are nominal.

Wade International


Third Avenue, Halstead, Essex, CO9 2SX.

Telephone: +44 (0)1787 475151 Fax: +44 (0)1787 475579

e-mail: wadetech@alumascwms.co.uk website: <https://www.alumascwms.co.uk/brands/wade/>

Typical Installation for K2302:

Note: This illustration may show a similar Wade Product - it is intended to show the general installation type only.



Dimensioned Section for K2302:

