


## Product Details

### Q1436 Bell Trapped Body Assembly

### Technical Data



#### Dimensions:

300 square at finish level

300 square body

325 - Overall Height

**Connection** - 6" BS416, 150mm DIN19522 / Harmer SML

**Free Area** - 176cm<sup>2</sup>

**Materials** - Stainless steel

**Weight** - 6.2 kg

#### General Description:

300 Square Stainless Steel Q series Stainless Steel Gully Bell Trapped Body Assembly, for use with tiles, marble, terrazzo, resin etc. flooring (with Optional Side Inlets and Optional Grade 316), with 162 dia. vertical outlet. Note: Gully is shown with grating which must be specified separately

#### Options:

To specify an option, add option letter(s) as a suffix to the Spec. Code

B - filter bucket

M - grade 316 stainless steel

N - non trapped version (supplied without bell trap assembly)

V - backwater valve

#### Materials:

**Stainless Steel - Austenitic Grade 304 (Grade 316 optional on most products):** Used for bodies, gratings, funnels, access covers, filter buckets and fixings. A corrosion-resistant metal containing significant amounts of nickel and chromium; AISI grade 304 stainless steel is used as standard, which is suitable for general use in and around buildings including most coastal locations. In applications such as swimming pools or having an aggressive atmosphere, grade 316 is recommended and is available optionally (if available, code 'M' will be listed under 'Options'). An even higher grade may be required for applications in highly corrosive environments including where exposure to seawater may be anticipated. Clean with soap and warm water rinse and wipe dry. Gratings may also be cleaned in certain dishwashers. Under no circumstances treat with metal scouring pads, metal scrapers or wire wool as these will contaminate surfaces leaving rust spots. Take care to cover stainless steel items when site work is going on, to avoid contamination with rust-inducing particles such as when mild steel or cast iron items are being cut.

All dimensions are in millimetres unless stated. In line with general practice all dimensions shown are nominal.

Wade International

Third Avenue, Halstead, Essex, CO9 2SX.

Telephone: +44 (0)1787 475151

Fax: +44 (0)1787 475579

e-mail: [wadetech@alumascwms.co.uk](mailto:wadetech@alumascwms.co.uk)

website: <https://www.alumascwms.co.uk/brands/wade/>

### Typical Installation for Q1436:

Note: This illustration may show a similar Wade Product - it is intended to show the general installation type only.

